



## PRODUCT DATA SHEET

# QP SUPER 2T

### PRODUCT DESCRIPTION

QP SUPER 2T is an advanced synthetic blend two stroke oil that is formulated from highly refined base oils with synthetic component and low ash additive package to provide excellent low smoke engine performance.

QP SUPER 2T can be used in premix with gasoline or oil injection systems. It is specifically formulated for higher temperature applications such as air-cooled two cycle engines found in chain saws, weed cutters, grass mowers and small generators. It's special detergents offer excellent protection against ring sticking and exhaust port blocking for all of these applications.

### PRODUCT BENEFITS:

- Protects engine against mechanical and thermal breakdown
- Minimises spark plug and engine deposits
- Low smoke
- Prevents spark plug fouling
- Extends engine life

### TYPICAL PROPERTIES

Density @ 15°C ATSM D4052	0.853
Viscosity @ 40°C (cSt) ATSM D445	40.4
Viscosity @ 100°C (cSt) ASTM D445	7.6
Viscosity Index ASTM D2270	145
Pour Point (°C)	-39
Flash Point (°C)	120
Appearance	Light Red

### PERFORMANCE SPECIFICATIONS

API: TC

ISO: L-EGD

JASO: FD

All reasonable care has been taken in the preparation of the advice and information contained herein and is correct at the time of preparation; no liability whatsoever is accepted for any loss or damage as a consequence of the use of such advice and information contained herein. Buyers should always determine the suitability of products for their particular purpose. The information provided is a guide to industry and is not necessarily manufacturing specification which varies from time to time.